

United States Patent and Trademark Office

mn

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/805,338 .	03/22/2004	Shin-ichi Nishizono	1075.1254	8996
21171 STAAS & HA	7590 07/16/2007 LSEY LLP	•	EXAMINER ,	
SUITE 700			LEE, CHUN KUAN	
WASHINGTO	NK AVENUE, N.W. N, DC 20005		ART UNIT	PAPER NUMBER
,		. ,	2181	
	,	•	MAIL DATE	DELIVERY MODE
			07/16/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)					
	10/805,338	NISHIZONO ET AL.					
Office Action Summary	Examiner	Art Unit					
	Chun-Kuan (Mike) Lee	2181					
The MAILING DATE of this communication app Period for Reply	ears on the cover sheet with the c	orrespondence address					
A SHORTENED STATUTORY PERIOD FOR REPLY WHICHEVER IS LONGER, FROM THE MAILING DATE of time may be available under the provisions of 37 CFR 1.13 after SIX (6) MONTHS from the mailing date of this communication. If NO period for reply is specified above, the maximum statutory period was reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 36(a). In no event, however, may a reply be tin will apply and will expire SIX (6) MONTHS from cause the application to become ABANDONE	N. nely filed the mailing date of this communication. D (35 U.S.C. § 133).					
Status							
1) Responsive to communication(s) filed on 05/21	<u>1/2007</u> .						
2a) ☐ This action is FINAL . 2b) ☑ This	This action is FINAL . 2b)⊠ This action is non-final.						
	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is						
closed in accordance with the practice under E	x parte Quayle, 1935 C.D. 11, 48	53 O.G. 213.					
Disposition of Claims							
4)⊠ Claim(s) <u>1-28</u> is/are pending in the application.							
4a) Of the above claim(s) is/are withdrawn from consideration.							
5) Claim(s) is/are allowed.							
	☑ Claim(s) <u>1-28</u> is/are rejected.						
7) Claim(s) is/are objected to.	. 1 1						
8) Claim(s) are subject to restriction and/or	r election requirement.						
Application Papers							
9) The specification is objected to by the Examine	r. ·	1					
10)⊠ The drawing(s) filed on <u>22 March 2004</u> is/are: a)⊠ accepted or b)□ objected to by the Examiner.							
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).							
Replacement drawing sheet(s) including the correct	* * * * * * * * * * * * * * * * * * * *	,					
11) ☐ The oath or declaration is objected to by the Ex	aminer. Note the attached Office	Action or form PTO-152.					
Priority under 35 U.S.C. § 119							
12)⊠ Acknowledgment is made of a claim for foreign a)⊠ All b)□ Some * c)□ None of:)-(d) or (f).					
1. Certified copies of the priority documents		an Na					
2. Certified copies of the priority documents3. Copies of the certified copies of the priority	• •						
application from the International Bureau	· ·	ed in this National Stage					
* See the attached detailed Office action for a list	, ,,	ed.					
	÷ *						
Attachment(s)							
Notice of References Cited (PTO-892) Notice of Draftsperson's Patent Drawing Review (PTO-948)	4) Interview Summary Paper No(s)/Mail D						
3) Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date	5) Notice of Informal F 6) Other:						

DETAILED ACTION

CONTINUED EXAMINATION UNDER 37 CFR 1.114

1. A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 05/21/2007 has been entered.

RESPONSE TO ARGUMENTS

- 2. Applicant's arguments filed 05/21/2007 have been fully considered but they are not persuasive. Currently, claims 1-28 are pending for examination.
- 3. In response to applicant's arguments, on page 12, 3rd paragraph, regarding the amended claims 1, 10, 19 and 28 rejected under 35 U.S.C. 103(a) that the combination of references does not teach/suggest the amended claim limitation of "reconnection queue for enqueuing control blocks storing reconnection information on one or more input/output requests;" applicant's arguments have fully been considered, but are not found to be persuasive.

AAPA teaches reconnection queue for enqueuing control blocks storing reconnection information on one or more input/output request (Specification, p. 5, II. 5-

16 and p. 9, II. 5-16), wherein the enqueued I/O requests are issued for reconnection and each I/O request is controlled and regulated in order to obtain reconnection success; therefore, there is a queue of control blocks with reconnection information associated with the queue of I/O requests waiting for reconnection.

4. In response to applicant's arguments, on page 13, last paragraph, regarding the amended claims 1, 10, 19 and 28 rejected under 35 U.S.C. 103(a) that the combination of references does not teach/suggest the claimed limitation of "dynamically switching the system ... according to the number of the enqueued control blocks;" applicant's arguments have fully been considered, but are not found to be persuasive.

Please note that one cannot show nonobviousness by attacking references individually where the rejections are based on combinations of references. See *In re Keller*, 642 F.2d 413, 208 USPQ 871 (CCPA 1981); *In re Merck & Co.*, 800 F.2d 1091, 231 USPQ 375 (Fed. Cir. 1986). In this case, the examiner relied on the references as following for the teaching of the above claimed limitation:

AAPA teaches the number of the enqueued control blocks (Specification, p. 5, ll. 5-16 and p. 9, ll. 5-16), wherein the enqueued control blocks are associated with the number of enqueued I/O requests.

<u>Coates</u> teaches the dynamically switching of the system according to the number of enqueued buffered data (e.g. control blocks) (Fig. 5; col. 3, II. 36-50 and col. 11, II. 21-32), wherein base on the number of data buffered, the fullness of the buffer is determined, and base on the fullness of the buffer, the system is dynamically switched

(e.g. switching between the system operating at higher transmission rate and the system operating at lower transmission rate)

By combining <u>Coates</u> with AAPA, the resulting combination of the references teaches dynamically switching the system according to the number of the enqueued control blocks (i.e.data).

I. INFORMATION CONCERNING OATH/DECLARATION

Oath/Declaration

5. The applicant's oath/declaration has been reviewed by the examiner and is found to conform to the requirements prescribed in **37 C.F.R. 1.63.**

II. INFORMATION CONCERNING DRAWINGS

Drawings

6. The applicant's drawings submitted are acceptable for examination purposes.

III. REJECTIONS BASED ON PRIOR ART

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Art Unit: 2181

7. Claims 1-2, 9-11, 18-20 and 27-28 are rejected under 35 U.S.C. 103(a) as being unpatentable over <u>Applicant's Admitted Prior Art</u> (<u>AAPA</u>) in view of <u>Coates et al.</u> (US Patent 6,694,389).

8. As per claims 1, 10, 19 and 28, <u>AAPA</u> teach a storage apparatus and a reconnection controlling method comprising:

a physical device (Drawings, Fig. 6, ref. 2a); and

a storage controlling apparatus (i.e. controller) (Drawings, Fig. 6, ref. 3) disposed between said physical device and a host (Drawings, Fig. 6, ref. 4) to control an access from said host to said physical device (Specification, page 1, I. 22 to page 2, I. 2); said storage controlling apparatus comprising:

one or more host interface modules (Drawings, Fig. 6, ref. 20), connected to a plurality of channels (Drawings, Fig. 6, ref. 50) of said host through a plurality of paths belonging to the same path group, for controlling an interface with said host (Specification, page 2, II. 17-19);

a management module (Drawings, Fig. 6, ref. 20) for generally managing the whole of said storage controlling apparatus (Specification, page 2, II. 20-21); said management module comprising:

a reconnection queue for enqueuing control blocks storing reconnection information on one or more input/output requests among input/output requests from said channels of said host (Specification, p. 5, II. 5-16 and p. 9, II. 5-16), wherein the enqueued I/O requests are issued

Application/Control Number: 10/805,338

Art Unit: 2181

for reconnection and each I/O request is controlled and regulated in order to obtain reconnection success; therefore, there it would be obvious to include the queue of control blocks with reconnection information associated with the queue of I/O requests waiting for reconnection; and

Page 6

a controlling mean, when an I/O process corresponding to one of said one or more control blocks managed in said reconnection queue is resumed, for controlling resumption of said I/O process in either

a first system of issuing a reconnection request to each of said paths belonging to the same path group one by one through said host interface module and requesting said host interface module to perform said I/O process using a path first successful in reconnection at the point of time that the reconnection succeeds (Specification, page 7, II. 5-16), wherein the implementation of the first system would result in the lower transmission rate as the requesting is implemented one by one, or

a second system of issuing concurrently or almost concurrently the reconnection request to said plural paths belonging to the same path group through said one or more host interface modules and requesting said host interface module to perform said I/O process using a path which first succeeds in the reconnection (Specification, page 7, II. 17-26), wherein the implementation of the second system would result in the higher

Art Unit: 2181

transmission rate as the requesting may be implemented to more than one host interface module, and further more, there must be the controlling mean in order to properly operate in either the first system or the second system.

<u>AAPA</u> does not expressly teach the storage apparatus and the reconnection controlling method comprising wherein said management module comprising:

the control means for the first system and the second system;

a monitoring means for monitoring the number of said enqueued control blocks in said reconnection queue; and

a switching means for dynamically switching the system to be executed by said controlling means to either said first system or said second system according to the number of the enqueued control blocks monitored by said monitoring means.

Coates teaches a method and a apparatus for data flow control comprsing:

determining the occupancy (e.g. fullness) of a buffer by counting the number of sub-buffers in a steady state of starvation and congestion (col. 11, II. 21-32); and determining if the fullness of the buffer is above an upper threshold (Fig. 5, ref. 500 and col. 3, II. 36-50);

signaling the receiver regarding the increase of transmission rate if the fullness of the buffer is above said upper threshold (Fig. 5, ref. 520 and col. 3, II. 36-50), therefore there would be an increase in the amount of data transferred from the buffer to the receiver;

determining if the fullness of the buffer is below an lower threshold (Fig. 5, ref. 530 and col. 3, II. 36-50);

signaling the receiver regarding the reduction of transmission rate if the fullness of the buffer is below said lower threshold (Fig. 5, ref. 540 and col. 3, II. 36-50), therefore there would be a reduction in the amount of data transferred from the buffer to the receiver, wherein the data flow control enables the switching between operating at transferring the increased amount of data and operating at transferring the reduced amount of data.

It would have been obvious to one of ordinary skill in this art, at the time of invention was made to include <u>Coates</u>'s buffer flow control into <u>AAPA</u>'s management module's queuing of the requests. The resulting combination of the references teaches the storage apparatus and the reconnection controlling method further comprising:

monitoring by determining the fullness of the buffer enqueuing the control blocks on one or more input/output requests by counting the number of the euqueued control blocks:

determining if the number of control blocks in the reconnection queue is greater than the limitation, and if it is determined to be greater, more requests would be transferred (increasing the amount of requests from the buffer to the receiver), therefore would operate the control mean for the second system (i.e. scattering mode) as multiple requests are concurrently issued and transferred from the buffer to the receiver (e.g. host);

determining if the number of control blocks in the reconnection queue is lesser than the limitation, and if it is determined to be lesser, less request would be transferred (reducing the amount of requests from the buffer to the receiver), therefore operating the control mean for the first system (i.e. one path mode) as requests are issued and transferred one at a time from the buffer to the receiver; and

switching between operating at the second system (e.g. transferring more requests) and operating at the first system (e.g. transferring lesser requests) base on the fullness of the reconnection queue, therefore, the control means would operate in either the first system or the second system.

Therefore, it would have been obvious to combine <u>Coates</u> with <u>AAPA</u> for the benefit of implementing a robust flow control ensuring the buffer does not become full (congested) or empty (starved) during transmission of data (Coates, col. 1, II. 11-24).

9. As per claims 2, 11 and 20, <u>AAPA</u> and <u>Coates</u> teach all the limitations of claims 1, 10 and 19 as discussed above, where <u>Coates</u> further teaches the storage apparatus and the reconnection controlling method comprising:

wherein when said the number of the enqueued control blocks monitored by said monitoring means is not larger than a predetermined number (Fig. 5, ref. 530), said switching means switches the system to be executed by said controlling means to said first system (Fig. 5, ref. 540), and

when the number of the enqueued control blocks monitored by said monitoring means exceeds said predetermined number (Fig. 5, ref. 500), said switching means

switches the system to be executed by said controlling means to said second system (Fig. 5, ref. 520).

- 10. As per claims 9, 18 and 27, <u>AAPA</u> and <u>Coates</u> teach all the limitations of claims 1, 10 and 19 as discussed above, where <u>AAPA</u> further teaches the storage apparatus and the reconnection controlling method comprising wherein when said second system is executed, said controlling means successively requests the second and later paths which succeed in the reconnection to perform the I/O processes corresponding to one ore more control blocks which can be reconnected among said control blocks managed in said reconnection queue (<u>AAPA</u>, Specification, page 7, I. 17 to page 9, I. 1).
- 11. Claims 3-8, 12-17 and 21-26 are rejected under 35 U.S.C. 103(a) as being unpatentable over <u>Applicant's Admitted Prior Art (AAPA)</u> and <u>Coates et al.</u> (US Patent 6,694,389), and further in view of <u>Mizuno</u> (US Patent 6,922,743).

AAPA and Coates teach all the limitations of claims 1, 10 and 19 as discussed above.

<u>AAPA</u> and <u>Coates</u> does not teach the storage apparatus and the reconnection controlling method further comprising:

wherein said management module further comprises a management table for managing a use status of each of said paths through said one or more host interface modules; and

when either said first system or said second system is executed, said controlling means refers to said management table to issue the reconnection request to the corresponding paths set free in said management table through said host interface module.

Mizuno teaches a system and a method comprising:

a controller (Fig. 5, ref. 530) comprising a cross-call administration table (Fig. 5, ref. 540); and

wherein the cross-call administration table provides the status of a port (e.g. ready flag) that a I/O path is connected to (Fig. 8, ref. 825, 835), and further more, the cross-call administration table is read out to determine which of the channel control processors (Fig. 5, ref. 505) controlling the ports are not busy in order to carry out the reconnection process (col. 9, II. 13-26).

It would have been obvious to one of ordinary skill in this art, at the time of invention was made to include <u>Mizuno</u>'s cross-call administration table and the corresponding ready flag into <u>AAPA</u> and <u>Coates</u>'s management module. The resulting combination of the references teaches the storage apparatus and the reconnection controlling method further comprising:

the management module comprises the cross-call administration table with the ready flag; and

when operating in either the first system or the second system, the control mean reads out the cross-call administration table in order to determine, through the host

Art Unit: 2181

interface module (e.g. channel control processors), which of the I/O path is not busy to implement the reconnection process.

Therefore, it would have been obvious to combine <u>Mizuno</u> with <u>AAPA</u> and <u>Coates</u> for the benefit of increasing the data throughput to the host as the response to the host's request can be made rapidly (<u>Mizuno</u>, col. 4, II. 39-43).

IV. CLOSING COMMENTS

Conclusion

a. STATUS OF CLAIMS IN THE APPLICATION

The following is a summary of the treatment and status of all claims in the application as recommended by M.P.E.P. 707.07(i):

a(1) CLAIMS REJECTED IN THE APPLICATION

Per the instant office action, claims 1-28 have received a first action on the merits and are subject of a first action non-final.

b. <u>DIRECTION OF FUTURE CORRESPONDENCES</u>

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Chun-Kuan (Mike) Lee whose telephone number is (571) 272-0671. The examiner can normally be reached on 8AM to 5PM.

IMPORTANT NOTE

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Alford Kindred can be reached on (571) 272-4037. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2181

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

July 2, 2007

Chun-Kuan (Mike) Lee

Examiner Art Unit 2181

ALFORD KINDRED
PRIMARY EXAMINER